



1. Dimensions:



UL1950 approved for the requirements of Supplementary Insulation with 300 working volts. UL file #E165866

DOC. REV B/3

2.Schematic:



3.Electrical Specifications: @25°C

PIN1-5 OCL: 2.0mH ±6% @10KHz 0.1V 160mADC
(CONNECT PIN2-4)

PIN1-5 LL: 11uH Max @100KHz 100mV
(CONNECT PIN2-4, PIN7-9)

TURNS RATIO: Line:Chip = 2CS:1±1%

CW/W: PIN1-9 80pF Max. CONNECT PIN2-4

DC Res.: 2.5 Ohms Max (Line)

DC Res.: 1.0 Ohm Max (Chip)

THD: 70dB Min. @20KHz 4.5VP-P

RETURN LOSS: 16.5dB Min. @40KHz-300KHz

INSERTION LOSS: ±0.5dB @40KHz

LONGITUDINAL BALANCE: 50dB Min. @40KHz-300KHz

FREQ RESP: ±0.1dB, 33KHz-110KHz

ISOLATION VOLTAGE: 2500Vrms (Chip to Line)

TEMPERATURE RANGE: -40°C - +85°C

XFMRS Inc	Title: HDSL TRANSFORMER	
	UNLESS OTHERWISE SPECIFIED	P/N: XF1313-4HD REV. B
	TOLERANCES: .xxx ±0.010	DWN. 廖玉坤 Apr-17-00
	Dimensions in INCH	CHK. 李清儿 Apr-17-00
SHEET 1 OF 1	APP. Joe Huff	Apr-17-00