

XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB201209-220-6A				Rev: A/1		
DIMENSION : (m/m) <div style="text-align: center; margin: 10px 0;"> </div>				A	$\varnothing 2.0 \pm 0.2$	m/m
				B	1.2 ± 0.2	m/m
				C	0.9 ± 0.2	m/m
				D	0.5 ± 0.3	m/m
				E		m/m
				F		m/m
				G		m/m
				H		m/m
				I		m/m
				J		m/m
				K		m/m
				L		m/m
				M		m/m
				N		m/m
				O		m/m
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS		
Z	22 Ohms $\pm 25\%$	TEST FREQ.	100	MHz	<input type="radio"/> HP 34401A MULTIMETER <input type="radio"/> HP 4195 NETWORKS/SPECTRUM ANALYZER <input type="radio"/> HP 42841 BIAS CURRENT SOURCE <input type="radio"/> HP 4285A LCR METER <input type="radio"/> HP 4286A RF LCR METER <input checked="" type="radio"/> HP 4291A RF IMPEDANCE / MATERIAL ANALYZER <input type="radio"/> HP 4338A MILLION OHM METER <input type="radio"/> HP 6632A DC POWER SUPPLY <input type="radio"/> HP4284A PRECISION LCR METER	
Z		TEST FREQ.		MHz		
SRF		TEST FREQ.		MHz		
Rdc	0.020 Ohms Max	TEST FREQ.		MHz		
Idc	6000mA Max	TEST FREQ.		MHz		
		TEST FREQ.				
DRAWN BY :		CHECKED BY :		APPROVED BY :		
ISAIAH MCNEIL		TONY IMBURGIA		JOE HUFF		
				12-01-03		