



XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB201209-222				Rev: A/2		
<p style="margin: 0;">DIMENSION : (m/m)</p> <div style="text-align: center; margin: 10px 0;">  </div> <div style="text-align: center; margin: 10px 0;">  </div>				A	Ø2.0±0.2	m/m
				B	1.2±0.2	m/m
				C	0.9±0.2	m/m
				D	0.5±0.3	m/m
				E		m/m
				F		m/m
				G		m/m
				H		m/m
				I		m/m
				J		m/m
				K		m/m
				L		m/m
				M		m/m
				N		m/m
O		m/m				
ELECTRICAL REQUIREMENTS				TEST INSTRUMENTS		
Z	2250±25% ohm	TEST FREQ.	100 MHz	<ul style="list-style-type: none"> ○ HP 34401A MULTIMETER ○ HP 4195 NETWORKS/SPECTRUM ANALYZER ○ HP 42841 BIAS CURRENT SOURCE ○ HP 4285A LCR METER ○ HP 4286A RF LCR METER ● HP 4291A RF IMPEDANCE / MATERIAL ANALYZER ○ HP 4338A MILLION OHM METER ○ HP 6632A DC POWER SUPPLY ○ HP4284A PRECISION LCR METER 		
Rdc	0.600 OHMS MAX.	TEST FREQ.	MHz			
Idc	200mA MAX.	TEST FREQ.	MHz			
<p style="margin: 0;">Notes:</p> <ol style="list-style-type: none"> 1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability. 2. Flammability: UL94V-0 3. ASTM oxygen index: > 28% 4. Insulation System: Class F 155°C. UL file E151556 5. Operating Temperature Range: All listed parameters are to be within tolerance from -55°C to +125°C 6. Storage Temperature Range: -55°C to +125°C 7. Aqueous wash compatible 						
DRAWN BY :		CHECKED BY :		APPROVED BY :		
BUDDY WOODS		JOE HUFF		TONY IMBURGIA		