


XFMRS, Inc.

SPECIFICATION FOR APPROVAL

XFMRS P/N : XFEB453215-115-2A Rev: A

<p>DIMENSION : (m/m)</p> 	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>A</td><td>$\varnothing 4.5 \pm 0.2$</td><td>m/m</td></tr> <tr><td>B</td><td>3.2 ± 0.2</td><td>m/m</td></tr> <tr><td>C</td><td>1.5 ± 0.2</td><td>m/m</td></tr> <tr><td>D</td><td>0.5 ± 0.3</td><td>m/m</td></tr> <tr><td>E</td><td></td><td>m/m</td></tr> <tr><td>F</td><td></td><td>m/m</td></tr> <tr><td>G</td><td></td><td>m/m</td></tr> <tr><td>H</td><td></td><td>m/m</td></tr> <tr><td>I</td><td></td><td>m/m</td></tr> <tr><td>J</td><td></td><td>m/m</td></tr> <tr><td>K</td><td></td><td>m/m</td></tr> <tr><td>L</td><td></td><td>m/m</td></tr> <tr><td>M</td><td></td><td>m/m</td></tr> <tr><td>N</td><td></td><td>m/m</td></tr> <tr><td>O</td><td></td><td>m/m</td></tr> </table>	A	$\varnothing 4.5 \pm 0.2$	m/m	B	3.2 ± 0.2	m/m	C	1.5 ± 0.2	m/m	D	0.5 ± 0.3	m/m	E		m/m	F		m/m	G		m/m	H		m/m	I		m/m	J		m/m	K		m/m	L		m/m	M		m/m	N		m/m	O		m/m
A	$\varnothing 4.5 \pm 0.2$	m/m																																												
B	3.2 ± 0.2	m/m																																												
C	1.5 ± 0.2	m/m																																												
D	0.5 ± 0.3	m/m																																												
E		m/m																																												
F		m/m																																												
G		m/m																																												
H		m/m																																												
I		m/m																																												
J		m/m																																												
K		m/m																																												
L		m/m																																												
M		m/m																																												
N		m/m																																												
O		m/m																																												

ELECTRICAL REQUIREMENTS	TEST INSTRUMENTS
-------------------------	------------------

Z	115±25% Ohms	TEST FREQ.	100	MHz	<input type="radio"/> HP 34401A MULTIMETER <input type="radio"/> HP 4195 NETWORKS/SPECTRUM ANALYZER <input type="radio"/> HP 42841 BIAS CURRENT SOURCE <input type="radio"/> HP 4285A LCR METER <input type="radio"/> HP 4286A RF LCR METER <input checked="" type="radio"/> HP 4291A RF IMPEDANCE / MATERIAL ANALYZER <input type="radio"/> HP 4338A MILLION OHM METER <input type="radio"/> HP 6632A DC POWER SUPPLY <input type="radio"/> HP4284A PRECISION LCR METER
Rdc	0.10 Ohms Max	TEST FREQ.		MHz	
Idc	2000mAdc Max	TEST FREQ.		MHz	

- Notes:**
1. Solderability: Leads shall meet MIL-STD-202, Method 208D for solderability.
 2. Flammability: UL94V-0
 3. ASTM oxygen index: > 28%
 4. Insulation System: Class F 155°C. UL file E151556
 5. Operating Temperature Range: All listed parameters are to be within tolerance from -40°C to +85°C
 6. Storage Temperature Range: -55°C to +125°C
 7. Aqueous wash compatible
 8. SMD Lead Coplanarity: ±0.004"(D.102mm)
 9. Moisture Sensitivity: Level 2

DRAWN BY : BUDDY WOODS	CHECKED BY : JOE HUFF	APPROVED BY : J Ng
------------------------------	--------------------------	-----------------------